

www.paceillumination.com

**Filename:** EURO3 24 CFLIII-7

**Manufacturer:** PACE ILLUMINATION CORP. VANCOUVER, B.C.

**Luminaire:** PACE 24" EUROPE LUMINAIRE WITH TYPE III REFLECTOR AND FLAT CLEAR GLASS LENS

**Luminaire Cat:** EURO3-4050-24"-175MH-CFL-III

**Lamp:** ONE 175W CLEAR METAL HALIDE LAMP. LUMEN RATING = 14000 LMS.

**Lamp Output:** 1 lamp(s), rated Lumens/lamp: 14000

**Max Candela:** 4,839.1 at Horizontal: 75°, Vertical: 60°

**Input Wattage:** 1

**Luminous Opening:** Circular (Dia: 2ft)

**Test:** Based on LSCA066


**Test Lab:** Lighting Sciences Canada Ltd. 440 Phillip St., Unit 19 Waterloo, Ontario

**Photometry :** Type C

**CIE Class:** Direct

**Cutoff Class:** Full Cutoff

**Nema Type:** 7 X 6



**Zonal Lumen Summary**

Zone	Lumens	% Lamp	% Luminaire
0-30	1,582.1	11.3%	17.3%
0-40	2,922.0	20.9%	32%
0-60	6,637.2	47.4%	72.7%
60-90	2,497.8	17.8%	27.3%
70-100	686.2	4.9%	7.5%
90-120	0	0%	0%
0-90	9,135.0	65.2%	100%
90-180	0	0%	0%
0-180	9,135.0	65.2%	100%

**Lumens Per Zone**

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	175.5	1.9%	90-100	0	0%
10-20	517.0	5.7%	100-110	0	0%
20-30	889.5	9.7%	110-120	0	0%
30-40	1,339.9	14.7%	120-130	0	0%
40-50	1,777.6	19.5%	130-140	0	0%
50-60	1,937.6	21.2%	140-150	0	0%
60-70	1,811.6	19.8%	150-160	0	0%
70-80	681.8	7.5%	160-170	0	0%
80-90	4.4	0.0%	170-180	0	0%



**Luminaire Report Summary**

IESNA:LM-63-2002  
[TEST] Based on LSCA066  
[TESTLAB] Lighting Sciences Canada Ltd.  
[MORE] 440 Phillip St., Unit 19  
[MORE] Waterloo, Ontario  
[ISSUE DATE] 01-20-2004  
[MANUFAC] PACE ILLUMINATION CORP.  
[MORE] VANCOUVER, B.C.  
[LUMCAT] EURO3-4050-24"-175MH-CFL-III  
[LUMINAIRE] PACE 24" EUROPE LUMINAIRE  
[MORE] WITH TYPE III REFLECTOR AND FLAT CLEAR GLASS LENS  
[LAMP] ONE 175W CLEAR METAL HALIDE LAMP. LUMEN RATING = 14000 LMS.  
FILE: CANDELA MULTIPLIER: 0.39  
FILE: VERTICAL ANGLES: 73, HORIZONTAL ANGLES: 145  
FILE: COORDINATE SYSTEM: TYPE C  
FILE: UNIT OF MEASURE: STANDARD  
FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.12 copyright 2003-2011 by jSolutions, Inc.  
Reported data calculated from manufacturer's data file, based on IES recommended methods.