CILINDRO

EUDC III - Wall Mount.



PROJECT DATE

COMMENTS

STANDARD FEATURES

- Heavy Gauge Spun Aluminum Housing.
- Clear Flat Lens Standard.
- Down or Up&Down LED light.
- Outdoor Waterproof IP65.
- Efficacy, 129 lumens/ watt, (10w to 100w).














SERIES	MODEL	SIZE	LAMP	LUMENS	сст	VOLT	CONTROL	COLOR	MOUNTING	OPTIONS
EUDC-WM	III	6 = 6" Diam.	LED		K27 = 2700K K3 = 3000K K35 = 3500K K4 = 4000K K5 = 5000K	120/277 UNV	DD= 0-10V Dimming driver	TBK= Textured-Black CC = Custom Color RAL = RAL Color	DL= Downlight U/D= Up& Downlight	MS = Motion Sensor. EM = Emergency Backup. PE1 = Photocell 120V. PE2 = Photocell 277V.
ORDERING INFORMATION										
SERIES	MODEL	SIZE	LAMP	LUMENS	сст	VOLT	CONTROL	COLOR	MOUNTING	OPTIONS

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- Programmable drivers at the PACE factory
- Color tunable
- Capable of remote dimming

- Can be equipped with motion sensors for on/off functioning Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS







SIZES

• 6" diameter

MOUNTING

Formed aluminum arm with wall plate

U/D Wall Arm

Mounts to standard 4" J-Box

COLOR

- Textured or smooth polyester powder coat finishes RAL colors available

DIMENSIONS

8.00" 6.25" 12"



